

MIL-C-17G QPL Cable

50 Ohm Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation			
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m	
30 AWG Stranded (7x38) .012" Silver-plated Copper-covered Steel Conductor • Silver-plated Copper Braid Shield (96% Coverage)																				
TFE Teflon® Insulation • White FEP Jacket																				
200°C	83265	—	100†	30.5	.8	.4	30 AWG	.033	.84	SPC Braid	.071	1.80	50	69.5%	29.0	95.1	1	2.6	8.5	
VW-1			500†	152.4	4.0	1.6	(7x38)			96% Shield								10	5.6	18.4
			1000†	304.8	6.0	3.2	.012"			Coverage									50	10.5
									SPCCS	14.6Ω/M'								100	14.0	45.9
									244.0Ω/M'	47.9Ω/km								200	19.0	62.3
									801.0Ω/km									400	28.0	91.9
																		700	37.0	121.4
																		900	42.5	139.4
																		1000	46.0	150.9

M17/169-00001 (RG-178B/U). Non-SWR swept version of RG-178.

26 AWG Stranded (7x34) .020" Silver-plated Copper-covered Steel Conductor • Silver-plated Copper Braid Shield (95% Coverage)																					
TFE Teflon Insulation • White FEP Jacket																					
200°C	83284	—	100†	30.5	1.2	.5	26 AWG	.058	1.47	SPC Braid	.098	2.49	50	69.5%	29.0	95.1	1	1.2	3.9		
VW-1			500†	152.4	5.5	2.7	(7x34)			95% Shield									10	2.7	8.9
			1000†	304.8	11.0	5.0	.020"			Coverage										50	5.6
									SPCCS	6.5Ω/M'								100	8.3	27.2	
									84.1Ω/M'	21.3Ω/km								200	12.0	39.4	
									275.9Ω/km									400	17.5	57.4	
																		700	23.7	77.8	
																		900	27.3	89.6	
																		1000	29.0	95.1	

M17/172-00001 (RG-316/U). Non-SWR swept version of RG-316.

26 AWG Stranded (7x34) .020" Silver-plated Copper-covered Steel Conductor • Silver-plated Copper Braid Shield (95% Coverage)																					
TFE Teflon Insulation • Brown FEP Jacket																					
200°C	84316	—	100†	30.5	1.2	.5	26 AWG	.058	1.47	SPC Braid	.098	2.49	50	69.5%	29.0	95.1	1	1.2	3.9		
VW-1			500†	152.4	5.5	2.5	(7x34)			95% Shield									10	2.7	8.9
			1000†	304.8	11.0	5.0	.020"			Coverage										50	5.6
									SPCCS	6.5Ω/M'								100	8.3	27.2	
									84.1Ω/M'	21.3Ω/km								200	12.0	39.4	
									275.9Ω/km									400	17.5	57.4	
																		700	23.7	77.8	
																		900	27.3	89.6	
																		1000	29.0	95.1	

M17/113-RG316

22 AWG Stranded (27x36) .030" Tinned Copper Conductor • Tinned Copper Braid Shield (95% Coverage)																					
Polyethylene Insulation • Black Non-contaminating PVC Jacket																					
UL AWM	9252	NEC:	1000	304.8	18.0	8.2	22 AWG	.096	2.44	TC Braid	.160	4.06	50	66%	30.8	101.0	1	.4	1.3		
Style 1354		CMX					(27x36)			Shield									10	1.7	5.6
(30V 80°C)		CEC:					.030"			95% Shield									50	4.5	14.8
VW-1	CMX					TC			Coverage									100	7.0	23.0	
						17.1Ω/M'			5.2Ω/M'									200	11.0	36.1	
						56.1Ω/km			17.1Ω/km									400	16.5	54.1	
																		700	23.5	77.1	
																		900	27.3	89.6	
																		1000	29.0	95.1	

M17/157-00001 (RG-122/U). Non-SWR swept version of RG-122.

DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • SPC = Silver-plated Copper • SPCCS = Silver-plated Copper-covered Steel • TC = Tinned Copper • TFE = Tetra Fluoroethylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

†May contain more than one piece, minimum length of any one piece is 25 ft.

Teflon is a DuPont trademark.



MIL-C-17G QPL Cable

50 Ohm Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

20 AWG Stranded (19x33) .035" Tinned Copper Conductor • Tinned Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket

85°C	9203	—	500	152.4	12.5	5.7	20 AWG (19x33) .035" TC 10.8Ω/M' 35.4Ω/km	.116	2.95	TC Braid 95% Shield Coverage 4.1Ω/M' 13.5Ω/km	.195	4.95	50	66%	30.8	101.0	1	.4	1.3
			1000	304.8	25.0	12.3											10	1.4	4.6
																50	3.3	10.8	
																100	4.9	16.1	
																200	7.3	24.0	
																400	11.5	37.7	
																700	17.0	55.8	
																900	20.0	65.6	
																1000	21.5	70.5	

M17/28-RG58

85°C	8262	—	U-500	U-152.4	13.5	6.1	20 AWG (19x33) .035" TC 10.8Ω/M' 35.4Ω/km	.115	2.92	TC Braid 95% Shield Coverage 4.1Ω/M' 13.5Ω/km	.195	4.95	50	66%	30.8	101.0	1	.4	1.3
			500	152.4	12.5	5.7											10	1.4	4.6
			U-1000	U-304.8	26.0	11.8										50	3.3	10.8	
			1000	304.8	25.0	11.3										100	4.9	16.1	
																200	7.3	24.0	
																400	11.5	37.7	
																700	17.0	55.8	
																900	20.0	65.6	
																1000	21.5	70.5	

M17/155-00001 (RG-58C/U). Non-SWR swept version of RG-58.

19 AWG Solid .034" Silver-coated Copper Conductor • Double Silver-coated Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket

UL AWM Style 1354 (30V 60°C)	9273	NEC:	100	30.5	4.7	2.1	19 AWG (solid) .034" SCC 8.8Ω/M' 28.9Ω/km	.117	2.97	(2) SCC Braids 95% Shield Coverage 2.5Ω/M' 8.2Ω/km	.212	5.39	50	66%	30.8	101.0	1	.4	1.3
		CMX	U-500	U-152.4	20.0	9.1											10	1.2	3.9
		CEC:	500	152.4	18.5	8.4										50	2.8	9.2	
		CMX	U-1000	U-304.8	39.0	17.7										100	4.1	13.5	
			1000	304.8	37.0	16.8										200	6.0	19.7	
																400	8.8	28.9	
																700	12.0	39.4	
																900	13.8	45.3	
																1000	14.5	47.6	

M17/167-00001 (RG-223/U). Non-SWR swept version of RG-223.

18 AWG Solid .037" Silver-coated Copper-covered Steel Conductor • Double Silver-coated Copper Braid Shield (96% Coverage)

Plenum • TFE Teflon® Insulation • Tinted Brown FEP Jacket

200°C VW-1	84142	NEC:	100	30.5	5.0	2.3	18 AWG (solid) .037" SCCCS 19.3Ω/M' 63.3Ω/km	.116	2.95	(2) SCC Braids 96% Shield Coverage 2.3Ω/M' 7.5Ω/km	.195	4.95	50	70%	29.0	95.1	10	1.1	3.6
		CMP	500†	152.4	22.5	10.2											50	2.6	8.5
		CEC:	1000†	304.8	46.0	20.9										100	3.8	12.5	
																200	5.4	17.7	
																400	7.9	25.9	
																700	10.7	35.1	
																900	12.3	40.4	
																1000	13.1	43.0	
																2000	19.3	63.3	

M17/60-RG142

200°C VW-1	83242	NEC:	100†	30.5	5.3	2.4	18 AWG (solid) .037" SCCCS 19.3Ω/M' 63.3Ω/km	.116	2.95	(2) SCC Braids 96% Shield Coverage 2.3Ω/M' 7.5Ω/km	.195	4.95	50	70%	29.0	95.1	10	1.1	3.6
		CMP	500†	152.4	22.5	10.2											50	2.6	8.5
		CEC:	1000†	304.8	46.0	20.9										100	3.8	12.5	
																200	5.4	17.7	
																400	7.9	25.9	
																700	10.7	35.1	
																900	12.3	40.4	
																1000	13.1	43.0	
																2000	19.3	63.3	

M17/158-00001 (RG-142B/U). Non-SWR swept version of RG-142.

18 AWG Solid .037" Silver-coated Copper-covered Steel Conductor • Silver-coated Copper Braid Shield (95% Coverage)

Plenum • TFE Teflon Insulation • Tinted Brown FEP Jacket

200°C VW-1	84303	NEC:	500†	152.4	16.5	7.5	18 AWG (solid) .037" SCCCS 16.3Ω/M' 53.5Ω/km	.116	2.95	SCC Braid Shield 95% Shield Coverage 4.3Ω/M' 14.1Ω/km	.170	4.31	50	70%	29.0	95.1	10	1.1	3.6
		CL2P	1000†	304.8	32.0	14.5											50	2.6	8.5
																100	3.8	12.5	
																200	5.4	17.7	
																400	7.9	25.9	
																700	10.7	35.1	
																900	12.3	40.4	
																1000	13.1	43.0	
																2000	19.3	63.3	

M17/111-RG303

DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • SCC = Silver-coated Copper • SCCCS = Silver-coated Copper-covered Steel • TC = Tinned Copper • TFE = Tetra Fluoroethylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

† May contain more than one piece, minimum length of any 1 piece is 25 feet.

Teflon is a DuPont trademark.



For more information, contact Belden Technical Support: **1-800-BELDEN-1** • www.belden.com


MIL-C-17G QPL Cable

50 Ohm Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

15.5 AWG Solid .056" Silver-plated Copper Conductor • Double Silver-plated Copper Braid Shield (95% Coverage)


Polyethylene Insulation • Black Non-contaminating PVC Jacket

85°C	9861	—	1000	304.8	91.0	41.4	15.5 AWG (solid)	.185	4.70	(2) SPC Braids	.332	8.43	50	66%	30.8	101.0	1	.3	.9
																			
																	10	.8	2.7
																	50	1.9	6.2
																	100	2.7	8.9
																	200	4.1	13.5
																	400	5.9	19.4
																	700	8.0	26.2
																	900	9.1	29.9
																	1000	9.8	32.2

M17/162-00001 (RG-212/U). Non-SWR swept version of RG-212.

13 AWG Stranded (7x21) .089" Bare Copper Conductor • Bare Copper Braid Shield (96% Coverage)


Polyethylene Insulation • Black Non-contaminating PVC Jacket

UL AWM Style 1354 (30V 60°C)	8267	NEC: CMX CEC: CMX	500	152.4	59.5	27.0	13 AWG (7x21)	.285	7.24	BC Braid	.405	10.29	50	66%	30.8	101.0	1	.2	.6
																			
																	10	.6	1.8
																	50	1.3	4.3
																	100	1.9	6.2
																	200	2.7	8.9
																	400	4.1	13.5
																	700	6.5	21.3
																	900	7.6	24.9
																	1000	8.0	26.2
																	4000	21.5	70.5

M17/163-00001 (RG-213/U). Non-SWR swept version of RG-213.

13 AWG Stranded (7x21) .089" Silver-plated Copper Conductor • Double Silver-plated Copper Braid Shield (97% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket

UL AWM Style 1354 (30V 60°C)	8268	NEC: CMX CEC: CMX	500	152.4	70.5	32.0	13 AWG (7x21)	.285	7.24	(2) SPC Braids	.425	10.80	50	66%	30.8	101.0	1	.2	.6
																			
																	10	.6	1.8
																	50	1.3	4.3
																	100	1.9	6.2
																	200	2.7	8.9
																	400	4.1	13.5
																	700	6.5	21.3
																	900	7.6	24.9
																	1000	8.0	26.2
																	4000	20.0	65.6

M17/164-00001 (RG-214/U). Non-SWR swept version of RG-214.

BC = Bare Copper • DCR = DC Resistance • SPC = Silver-plated Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

MIL-C-17G QPL Cable

75 Ohm Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

30 AWG Stranded (7x38) .012" Silver-plated Copper-covered Steel Conductor • Silver-plated Copper Braid Shield (94% Coverage)

TFE Teflon® Insulation • Tinted Brown FEP Jacket																				
200°C	83264	—	100†	30.5	1.2	.5	30 AWG (7x38)	.062	1.58	SPC Braid	.100	2.54	75	69.5%	19.5	64.0	1	3.0	9.8	
VW-1			500†	152.4	5.5	2.5			94% Shield								10	5.3	17.4	
				1000†	304.8	11.0	5.0	.012"			Coverage							50	8.5	27.9
								SPCCS			8.5Ω/M'							100	10.0	32.8
							244.0Ω/M'			27.4Ω/km							200	12.5	41.0	
							801.0Ω/km										400	16.0	52.5	
																	700	19.7	64.6	
																	900	22.3	73.2	
																	1000	24.0	78.7	

M17/94-RG179

23 AWG Solid .023" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket																			
60°C	9204	NEC:	500	152.4	18.0	8.2	23 AWG (solid)	.146	3.71	BC Braid	.241	6.12	75	66%	20.5	67.3	1	.6	2.0
VW-1		CMH	U-1000	U-304.8	38.0	17.3	.023"			95% Shield							10	1.1	3.6
		CEC:	1000	304.8	39.0	17.7	BCCS			Coverage							50	2.4	7.9
		CMH FT1					47.0Ω/M'			2.6Ω/M'							100	3.4	11.2
						154.2Ω/km			8.5Ω/km							200	4.9	16.1	
																400	7.0	23.0	
																700	9.7	31.8	
																900	11.1	36.4	
																1000	12.0	39.4	

M17/29-RG59

18 AWG Stranded (7x26) .048" Tinned Copper Conductor • Bare Copper Braid Shield (97% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket																			
60°C	9212	NEC:	1000	304.8	105.0	47.7	18 AWG (7x26)	.285	7.24	BC Braid	.405	10.29	75	66%	20.5	67.3	1	.2	.7
VW-1		CMH					.048"			97% Shield							10	.7	2.3
		CEC:					TC			Coverage							50	1.3	4.3
		CMH FT1					6.1Ω/M'			1.2Ω/M'							100	2.0	6.6
						20.0Ω/km			3.9Ω/km							200	2.9	9.5	
																400	4.2	13.8	
																700	5.8	19.0	
																900	6.9	22.6	
																1000	7.2	23.6	

M17/6-RG11

18 AWG Stranded (7x26) .048" Tinned Copper Conductor • Double Bare Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket																			
60°C	9850	NEC:	1000	304.8	131.0	59.5	18 AWG (7x26)	.285	7.24	(2) BC Braids	.425	10.80	75	66%	20.5	67.3	1	.2	.6
VW-1		CMH					.048"			95% Shield							10	.7	2.2
		CEC:					TC			Coverage							50	1.3	4.3
		CMH FT1					6.1Ω/M'			.8Ω/M'							100	2.0	6.6
						20.0Ω/km			2.6Ω/km							200	2.9	9.5	
																400	4.2	13.8	
																700	5.8	19.0	
																900	6.8	22.3	
																1000	7.1	23.3	

M17/77-RG216

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • SPCCS = Silver-plated Copper-covered Steel • TC = Tinned Copper • TFE = Tetra Fluoroethylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

†May contain more than one piece, minimum length of any 1 piece is 25 feet.

Teflon is a DuPont trademark.



For more information, contact Belden Technical Support: **1-800-BELDEN-1** • www.belden.com

MIL-C-17G QPL Cable

93 Ohm, 95 Ohm and 125 Ohm Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

93 Ohm • 22 AWG Solid .025" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (95% Coverage)

Semi-solid Polyethylene Insulation • Black Non-contaminating PVC Jacket																			
UL AWM Style 1354 (30V 60°C)	9862	NEC: CMX CEC: CMX	1000	304.8	37.0	16.8	22 AWG (solid) .025" BCCS 41.2Ω/M' 135.2Ω/km	.146	3.71	BC Braid 95% Shield Coverage 2.9Ω/M' 9.5Ω/km	.242	6.15	93	84%	13.5	44.3	1	.3	1.0
																	10	.9	3.0
																	50	1.9	6.2
																	100	2.7	8.9
																	200	3.8	12.5
																	400	5.3	17.4
																	700	7.3	24.0
																	900	8.2	26.9
																	1000	8.7	28.5

M17/30-RG62

93 Ohm • 22 AWG Solid .025" Bare Copper-covered Steel Conductor • BC Outer Braid/TC Inner Braid Shield (95% Coverage)

Semi-solid Polyethylene Insulation • Black Polyethylene Jacket																			
85°C	9169	—	1000	304.8	46.0	20.9	22 AWG (solid) .025" BCCS 41.2Ω/M' 135.2Ω/km	.146	3.71	(2) Braids Inner: BC Outer: TC 95% Shield Coverage 1.5Ω/M' 4.9Ω/km	.245	6.22	93	84%	13.5	44.3	1	.3	1.0
																	10	.9	3.0
																	50	1.9	6.2
																	100	2.7	8.9
																	200	3.8	12.5
																	400	5.3	17.4
																	700	7.3	24.0
																	900	8.2	26.9
																	1000	8.7	28.5

M17/90-RG71

95 Ohm • 30 AWG Stranded (7x38) .012" Silver-plated Copper-covered Steel Conductor • Silver-plated Copper Braid Shield (91% Coverage)

TFE Teflon® Insulation • Tinted Brown FEP Jacket																			
200°C VW-1	83266	—	1000†	304.8	20.0	9.1	30 AWG (7x38) .012" SPCCS 244.0Ω/M' 801.0Ω/km	.102	2.60	SPC Braid 91% Shield Coverage 6.5Ω/M' 21.3Ω/km	.141	3.58	95	69.5%	15.0	49.2	1	2.4	7.9
																	10	3.3	10.8
																	50	4.6	15.1
																	100	5.7	18.7
																	200	7.6	24.9
																	400	10.7	35.1
																	700	14.9	48.9
																	900	15.9	52.2
																	1000	17.0	55.8

M17/95-RG180

125 Ohm • 22 AWG Solid .025" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (97% Coverage)

Semi-solid Polyethylene Insulation • Black Non-contaminating PVC Jacket																			
60°C	9857	NEC: CMH CEC: CMH FT1	1000	304.8	94.0	42.6	22 AWG (solid) .025" BCCS 41.2Ω/M' 135.2Ω/km	.285	7.24	BC Braid 97% Shield Coverage 1.2Ω/M' 3.9Ω/km	.405	10.29	125	84%	9.7	31.8	1	.2	1.0
																	10	.5	1.6
																	50	1.1	3.6
																	100	1.5	4.9
																	200	2.3	7.5
																	400	3.4	11.2
																	700	4.6	15.1
																	900	5.5	18.0
																	1000	5.8	19.0

M17/31-RG63

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • SPC = Silver-plated Copper • SPCCS = Silver-plated Copper-covered Steel • TC = Tinned Copper • TFE = Tetra Fluoroethylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

†May contain more than 1 piece, minimum length of any one piece is 25 feet.

Teflon is a DuPont trademark.



For more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com**

MIL-C-17G QPL Cable

Twinax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

Twinax • 24 AWG Stranded (19x36) .024" Silver-coated High-Strength Copper Alloy Conductor • SCHSCA Braid Shield (93% Coverage)

TFE Teflon® Insulation • Blue PFA Jacket (Color Code: White, Blue)

200°C	81553	—	500 [†]	152.4	9.0	4.1	24 AWG (19x36)	.084	2.13	SCHSCA 93% Shield Coverage	.129	3.28	77	70%	24.0	78.7	1	1.2	3.9
			1000 [†]	304.8	16.0	7.3	.024" SCHSCA 24.0Ω/M' 78.7Ω/km			7.3Ω/M' 24.0Ω/km							10	4.0	13.1
																	50	9.2	30.2
																	100	13.0	42.7
																	200	18.4	60.4
																	400	26.1	85.6
																	700	34.6	113.5
																	900	39.3	128.9
																	1000	41.4	135.8

M17/176-00002

Twinax • 20 AWG Stranded (7x28) .038" Tinned Copper Conductor • Tinned Copper Braid Shield (85% Coverage)

Polyethylene Insulation • Black Non-contaminating PVC Jacket (One conductor has bare strand for ID)

85°C	9859	—	1000	304.8	33.0	15.0	20 AWG (7x28)	.158	4.01	TC Braid 85% Shield Coverage	.235	5.97	78	66%	19.7	64.6	1	.7	2.3
							.038" TC 9.5Ω/M' 31.2Ω/km			5.3Ω/M' 17.4Ω/km							10	2.3	7.5
																	50	5.2	17.1
																	100	7.5	24.6
																	200	11.0	36.1
																	400	16.0	52.5

M17/45-RG108

DCR = DC Resistance • PFA = Perfluoroalkoxy • SCHSCA = Silver-coated High-strength Copper Alloy • TC = Tinned Copper • TFE = Tetra Fluoroethylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

[†]Spools may contain more than one piece. Minimum length of any one piece is 50 ft. Length may vary ±10% from length shown for spools or reels and ±5% UnReel® cartons.

 Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

Teflon is a DuPont trademark.