

Standard Analog Video Cable

75 Ohm Miniature Coax



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

30 AWG Stranded (7x38) .012" Tinned Copper Conductor • Tinned Copper Braid Shield (89% Coverage)

Foam HDPE Insulation • Black PVC Jacket																			
UL AWM	9221	—	100	30.5	1.5	.7	30 AWG	.058	1.47	TC Braid	.097	2.46	75	78%	17.3	56.8	1	.7	2.3
Style 1375			U-500	U-152.4	4.0	1.8	(7x38)			89% Shield							3.6	1.3	4.3
(30V 60°C)			500	152.4	4.0	1.8	.012"			Coverage							4	1.3	4.3
							TC			11.7Ω/M'							5	1.6	5.2
							100.0Ω/M'			38.4Ω/km							7	1.9	6.2
							328.0Ω/km										9	2.1	6.9
																	10	2.2	7.2
																	50	5.1	16.7
																	70	6.1	20.0
																	100	7.3	23.9
																	200	10.5	34.4
																	400	15.5	50.9
																	700	21.5	70.5
																	900	24.8	81.4
																	1000	26.6	87.3

27 AWG Stranded (7x35) .017" Bare Copper-covered Steel Conductor • Tinned Copper Braid Shield (93% Coverage)

Polyethylene Insulation • Black PVC Jacket																			
UL AWM	8218	—	U-500	U-152.4	8.5	3.8	27 AWG	.100	2.54	TC Braid	.150	3.81	75	66%	20.5	67.3	1	1.2	3.9
Style 1354			500	152.4	8.0	3.6	(7x35)			93% Shield							10	2.4	7.9
(30V 60°C)			U-1000	U-304.8	16.0	7.3	.017"			Coverage							50	4.2	13.8
			1000	304.8	14.0	6.4	BCCS			5.7Ω/M'							100	5.7	18.7
							120.0Ω/M'			18.7Ω/km							200	8.3	27.2
							393.7Ω/km										400	12.1	39.7
																	700	16.5	54.1
																	900	19.0	62.3
																	1000	20.0	65.6

Miniature • 25 AWG Solid .018" Tinned Copper Conductors • Duobond® (100% Coverage) + TC Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • Black PVC Jacket																				
UL AWM	1281R	new	1	1000	304.8	8.0	3.6	25 AWG	.074	1.88	Duobond (100%)	.114	2.90	75	80%	17.0	55.8	1	.5	1.7
								(solid)			+ 95%							5	1.2	3.8
								.018"			TC Braid							50	3.7	12.1
								TC			Sweep Tested							100	4.9	16.1
								34.0Ω/M'			5.4Ω/M'							200	6.7	22.0
								111.6Ω/km			17.7Ω/km							400	9.5	31.2
											Guaranteed Return Loss							700	13.4	44.0
											See page 6.48 for Bundled versions.							900	15.0	49.2
																		1000	15.8	51.8
																		3000	31.2	102.4

Plenum • FPFA Insulation • Black Flamarrest® Jacket																				
UL AWM	1282P	new	1	1000	304.8	10.0	4.5	25 AWG	.074	1.88	Duobond (100%)	.114	2.90	75	81%	17.0	55.8	1	.4	1.3
								(solid)			+ 95%							5	.9	3.0
								.018"			TC Braid							50	3.7	12.1
								TC			Sweep Tested							100	5.0	16.4
								31.8Ω/M'			5.8Ω/M'							200	7.0	23.0
								104.3Ω/km			19.0Ω/km							400	10.0	32.8
											Guaranteed Return Loss							700	14.5	47.6
											See page 6.48 for Bundled versions.							900	17.0	55.8
																		1000	17.5	57.4
																		3000	37.0	121.4

BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FPFA = Foam Perfluoroalkoxy • HDPE = High-density Polyethylene • TC = Tinned Copper

Standard Analog Video Cable

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

23 AWG Solid .023" Bare Copper or Bare Copper-covered Steel Conductor (see below) • Bare Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 75°C) VW-1	8241	NEC: CM	100	30.5	4.4	2.0	23 AWG (solid) .023"	.146	3.71	BC Braid 95% Shield Coverage	.240	6.10	75	66%	20.5	67.3	1	.6	2.0
			U-500	U-152.4	19.5	8.9											10	1.1	3.6
			500	152.4	18.5	8.4											50	2.4	7.9
			U-1000 [▲]	U-304.8	38.0	17.2	BCCS			2.6Ω/M'							100	3.4	11.2
			1000	304.8	40.0	18.1	49.0Ω/M'			8.5Ω/km							200	4.9	16.1
			2000	609.6	80.0	36.3	160.7Ω/km										400	7.0	23.0
			5000	1524.0	200.0	90.7											700	9.7	31.8
																	900	11.1	36.4
																	1000	12.0	39.4

[▲]U-1000 ft. put-up also available in Red, Yellow, Green, Lt. Blue, White or Orange.

Flame-retardant Semi-foam Polyethylene Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 75°C)	8241A	NEC: CMG CEC: CMG FT4	U-1000	U-304.8	40.0	18.1	23 AWG (solid) .023"	.146	3.71	BC Braid 95% Shield Coverage	.242	6.15	75	66%	20.5	67.3	1	.6	2.0
			1000	304.8	42.0	19.1											5	.9	3.0
							BCCS			2.6Ω/M'							10	1.1	3.6
							49.0Ω/M'			8.5Ω/km							50	2.4	7.9
							160.7Ω/km										100	3.4	11.2
																	200	4.9	16.1
																	400	7.0	23.0
																	700	10.1	33.1
																	900	11.7	38.4
																	1000	13.2	43.3

Suitable for Indoor and Outdoor applications.

Polyethylene Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 80°C)	8241B	NEC: CM CEC: CM	U-1000	U-304.8	36.0	16.3	23 AWG (solid) .023"	.146	3.71	BC Braid 95% Shield Coverage	.242	6.15	75	66%	20.5	67.3	1	.4	1.3
			1000	304.8	37.0	16.8											10	1.1	3.6
							BC			2.9Ω/M'							50	2.4	7.9
							20.4Ω/M'			9.5Ω/km							100	3.4	11.2
							66.9Ω/km										200	4.9	16.1
																	400	7.0	23.0
																	700	9.7	31.8
																	900	11.1	36.4
																	1000	12.0	39.4

Suitable for Indoor and Outdoor applications.

22 AWG Stranded (7x30) .030" Bare Copper Conductor • Bare Copper Braid Shield (95% Coverage)

Foam Polyethylene Insulation • PVC Jacket (Available in Matte Black, Red, Blue, Green, White, Gray or Yellow)																			
High-Flex 60°C	8241F	—	1000	304.8	35.0	15.9	22 AWG (7x30) .030"	.146	3.71	BC Braid 95% Shield Coverage	.242	6.15	75	78%	17.3	56.8	1	.3	1.0
																	10	.9	3.0
							BC			2.6Ω/M'							50	2.1	6.9
							15.0Ω/M'			8.5Ω/km							100	3.0	9.8
							49.2Ω/km										200	4.5	14.8
																	400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

23 AWG Solid .023" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (97% Coverage)

Plenum • FEP Insulation • Black FEP Jacket																			
200°C	88241	NEC: CMP CEC: CMP FT6	500 [†]	152.4	18.0	8.2	23 AWG (solid) .023"	.132	3.35	BC Braid 97% Shield Coverage	.190	4.83	75	69.5%	19.5	64.0	1	.5	1.6
			1000 [†]	304.8	36.0	16.3											10	1.0	3.3
							BCCS			2.6Ω/M'							50	2.3	7.5
							49.0Ω/M'			8.5Ω/km							100	3.3	10.8
							160.7Ω/km										200	5.2	17.1
																	400	8.4	27.6
																	700	11.6	38.0
																	900	13.8	45.3
																	1000	14.8	48.6

Suitable for Outdoor and Direct Burial applications.

Plenum • FEP Insulation • Natural Flammarrest® Jacket																			
75°C	82241	NEC: CMP CEC: CMP FT6	U-500 [†]	U-152.4	18.5	8.4	23 AWG (solid) .023"	.134	3.35	BC Braid 97% Shield Coverage	.190	4.83	75	69.5%	19.5	64.0	1	.5	1.6
			U-1000 [†]	U-304.8	36.0	16.3											10	1.0	3.3
			1000 [†]	304.8	34.0	15.4											50	2.3	7.5
							BCCS			2.6Ω/M'							100	3.3	10.8
							49.0Ω/M'			8.5Ω/km							200	5.2	17.1
							160.7Ω/km										400	8.4	27.6
																	700	11.6	38.0
																	900	13.8	45.3
																	1000	14.8	48.6

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**. Request quotations of RG/U cables not listed.

[†]Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.



For more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com**

Standard Analog Video Cable

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

22 AWG Solid Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black PVC Jacket

UL AWM	8263	NEC:	U-500	U-152.4	19.5	8.9	22 AWG	.146	3.71	BC Braid	.242	6.15	75	66%	20.5	67.3	1	.6	2.0
Style 1354		CMX:	U-1000	U-304.8	38.0	17.2	(solid)			95% Shield							10	1.1	3.6
(30V 60°C)		CEC:	1000	304.8	39.0	17.7	.023"			Coverage							50	2.4	7.9
		CMX:					BCCS			2.6Ω/M'							100	3.4	11.2
							49.0Ω/M'			8.5Ω/km							200	4.9	16.1
							160.7Ω/km										400	7.0	23.0
																	700	9.7	31.8
																	900	11.1	36.4
																	1000	12.0	39.4

Non-contaminating Black PVC Jacket. Suitable for Indoor and Outdoor applications.

Foam Polyethylene Insulation • Black PVC Jacket

75°C	8221	—	U-500	U-152.4	18.5	8.4	22 AWG	.146	3.71	BC Braid	.242	6.15	80	78%	16.3	53.5	1	.4	1.4
			500	152.4	17.0	7.7	(solid)			95% Shield							10	.9	3.0
			U-1000	U-304.8	36.0	16.3	.025"			Coverage							50	2.0	6.6
			1000	304.8	37.0	16.8	BCCS			2.6Ω/M'							100	2.9	9.5
							50.0Ω/M'			8.5Ω/km							200	4.1	13.5
							164.0Ω/km										400	5.9	19.4
																	700	7.8	25.6
																	900	8.8	28.9
																	1000	9.9	32.5

Suitable for Outdoor and Aerial applications when supported by a Messenger Wire.

22 AWG Solid Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (85% Coverage)

Polyethylene Insulation • Black PVC Jacket

UL AWM	9244	NEC:	U-500	U-152.4	18.0	8.2	22 AWG	.146	3.71	BC Braid	.242	6.15	75	66%	19.4	63.6	1	.6	2.0
Style 1354		CMX:	U-1000	U-304.8	35.0	15.9	(solid)			85% Shield							10	1.1	3.6
(30V 80°C)		CEC:	1000	304.8	36.0	16.3	.025"			Coverage							50	2.4	7.9
		CMX:	3280	1000.0	118.1	53.8	BCCS			4.5Ω/M'							100	3.4	11.2
							50.0Ω/M'			14.8Ω/km							200	4.9	16.1
							164.0Ω/km										400	7.0	23.0
																	700	9.7	31.8
																	900	11.1	36.4
																	1000	12.0	39.4

Suitable for Indoor and Outdoor applications.

22 AWG Stranded (7x30) .030" Bare Copper Conductor • Bare Copper Braid Shield (95% Coverage)

Foam Polyethylene Insulation • Black PVC Jacket

UL AWM	9659	NEC:	U-500	U-152.4	19.0	8.6	22 AWG	.146	3.71	BC Braid	.242	6.15	75	78%	17.3	56.7	1	.3	1.0
Style 1354		CMX:	U-1000	U-304.8	37.0	16.8	(7x30)			95% Shield							10	.9	3.0
(30V 60°C)		CEC:	1000	304.8	38.0	17.2	.030"			Coverage							50	2.1	6.9
VW-1		CMX:					BC			2.6Ω/M'							100	3.0	9.8
							15.0Ω/M'			8.5Ω/km							200	4.5	14.8
							49.2Ω/km										400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

Non-contaminating PVC Jacket. For CCTV applications. Suitable for Indoor and Outdoor applications.

UL AWM	9259	NEC:	100	30.5	4.1	1.9	22 AWG	.146	3.71	BC Braid	.241	6.12	75	78%	17.3	56.7	1	.3	1.0
Style 1354		CM	U-500	U-152.4	18.0	8.2	(7x30)			95% Shield							10	.9	3.0
(30V 80°C)		CEC:	500	152.4	16.5	7.5	.030"			Coverage							50	2.1	6.9
		CM	U-1000	U-304.8	35.0	15.9	BC			2.6Ω/M'							100	3.0	9.8
			1000	304.8	37.0	16.8	15.0Ω/M'			8.5Ω/km							200	4.5	14.8
							49.2Ω/km										400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

For CCTV applications. Suitable for Indoor and Outdoor applications.

Plenum • Foam FEP Insulation • Black FEP Jacket

200°C	89259	NEC:	100†	30.5	5.1	2.3	22 AWG	.135	3.43	BC Braid	.193	4.90	75	78%	17.3	56.7	1	.3	1.0
		CMP	500†	152.4	16.0	7.3	(7x30)			95% Shield							10	.9	3.0
		CEC:	1000†	304.8	32.0	14.5	.030"			Coverage							50	2.1	6.9
		CMP FT6					BC			2.6Ω/M'							100	3.0	9.8
							15.0Ω/M'			8.5Ω/km							200	4.5	14.8
							49.2Ω/km										400	6.6	21.7
																	700	9.0	29.5
																	900	10.1	33.1
																	1000	11.0	36.1

Suitable for Outdoor and Direct Burial applications.

†Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.

Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket

75°C	82259	NEC:	U-1000	U-304.8	31.0	14.1	22 AWG	.135	3.43	BC Braid	.193	4.90	75	78%	17.3	56.7	1	.3	1.0
		CMP	1000	304.8	30.0	13.6	(7x30)			95% Shield							10	.9	3.0
		CEC:					.030"			Coverage							50	2.1	6.9
		CMP FT6					BC			2.6Ω/M'							100	3.0	9.8
							15.0Ω/M'			8.5Ω/km							200	4.5	14.8
							49.2Ω/km										400	6.6	21.7
																	700	9.0	29.5
																	900	10.1	33.1
																	1000	11.0	36.1

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. 1-800-BELDEN-1. Request quotations of RG/U cables not listed.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Standard Analog Video Cable

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

20 AWG Solid .032" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (80% Coverage)

Foam Polyethylene Insulation • Black PVC Jacket																			
75°C	9240	—	1000	304.8	31.0	14.1	20 AWG (solid) .032" BCCS 44.5Ω/M' 146.0Ω/km	.143	3.63	BC Braid 80% Shield Coverage 5.6Ω/M' 18.4Ω/km	.241	6.12	75	78%	17.3	56.7	1	.6	2.0
																	10	1.0	3.3
																	50	2.1	6.9
																	100	3.0	9.8
																	200	4.5	14.8
																	400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

Suitable for Outdoor applications.

20 AWG Solid .032" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (95% Coverage)

Foam Polyethylene Insulation • Black Polyethylene Jacket																			
80°C	8212	—	U-500	U-152.4	16.5	7.5	20 AWG (solid) .032" BCCS 44.5Ω/M' 146.0Ω/km	.143	3.63	BC Braid 95% Shield Coverage 2.6Ω/M' 8.5Ω/km	.242	6.15	75	78%	17.3	56.7	1	.6	2.0
			500	152.4	15.0	6.8											10	1.0	3.3
			U-1000	U-304.8	31.0	14.1											50	2.1	6.9
			1000	304.8	33.0	15.0											100	3.0	9.8
																	200	4.5	14.8
																	400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

Suitable for Outdoor and Aerial applications when supported by a Messenger Wire.

Foam Polyethylene Insulation • Black PVC Jacket																			
80°C	9274	NEC: CM CEC: CM	500	152.4	15.5	7.0	20 AWG (solid) .032" BCCS 44.5Ω/M' 146.0Ω/km	.143	3.63	BC Braid 95% Shield Coverage 3.5Ω/M' 11.5Ω/km	.240	6.10	75	82%	16.3	53.5	1	.6	2.0
			1000	304.8	35.0	15.9											10	1.0	3.3
																	50	2.1	6.9
																	100	3.0	9.8
																	200	4.5	14.8
																	400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

Suitable for Outdoor applications.

20 AWG Solid .032" Bare Copper Conductor • Bare Copper Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 75°C)	1426A	NEC: CM	U-1000	U-304.8	35.0	15.9	20 AWG (solid) .032" BC 10.0Ω/M' 32.8Ω/km	.145	3.68	BC Braid 95% Shield Coverage 2.6Ω/M' 8.5Ω/km	.242	6.15	75	83%	16.3	53.5	1	.3	1.0
																	5	.7	2.1
																	10	.9	3.0
																	50	1.9	6.2
																	100	2.6	8.5
																	200	3.6	11.8
																	400	5.0	16.4
																	700	7.0	23.0
																	900	8.0	26.3
																	1000	8.5	27.9

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**. Request quotations of RG/U cables not listed.

Standard Analog Video Cable

RG-6/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

21 AWG Solid .028" Bare Copper-covered Steel Conductor • Double Bare Copper Braid Shields (98% Coverage)

Polyethylene Insulation • Black Polyethylene Jacket																			
MATV Cable 80°C	8215	—	1000	304.8	74.0	33.6	21 AWG (solid) .028"	.185	4.70	(2) BC Braids 98% Shield Coverage	.332	8.43	75	66%	20.5	67.2	1	.4	1.3
																	10	.8	2.6
																	50	1.9	6.2
																	100	2.7	8.9
																	200	4.1	13.4
																	400	5.9	19.4
																	700	8.1	26.6
																	900	9.4	30.8
																	1000	9.8	32.1



18 AWG Solid .037" Bare Copper Conductor • Double Bare Copper Braid Shields (98% Coverage)

Foam Polyethylene Insulation • Black PVC Jacket																			
80°C	9290	NEC: CM	1000	304.8	59.0	26.8	18 AWG (solid) .037"	.180	4.57	(2) BC Braids 98% Shield Coverage	.288	7.32	75	81%	17.3	56.7	1	.2	.7
																	10	.7	2.3
																	50	1.7	5.6
																	100	2.5	8.2
																	200	3.6	11.8
																	400	5.3	17.4
																	700	7.2	23.6
																	900	8.3	27.2
																	1000	8.8	28.9



Suitable for Indoor and Outdoor applications.

18 AWG Solid .040" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (65% Coverage)

Plenum • Foam FEP Insulation • Black FEP Jacket																			
200°C	89248	NEC: CMP	500†	152.4	15.0	6.8	18 AWG (solid) .040"	.170	4.32	Duofoil + 65% TC Braid	.222	5.64	75	82%	16.5	50.3	1	.3	1.0
																	10	.66	2.2
																	50	1.5	4.9
																	100	2.1	6.9
																	200	3.1	10.2
																	400	4.5	14.8
																	700	6.0	19.7
																	900	6.9	22.6
																	1000	7.3	23.9



Suitable for Outdoor and Direct Burial applications.

Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket																			
75°C	82248	NEC: CMP	U-1000†	U-304.8	29.0	13.2	18 AWG (solid) .040"	.170	4.32	Duofoil + 65% TC Braid	.222	5.64	75	82%	16.5	50.3	1	.3	1.0
																	10	.7	2.3
																	50	1.6	5.2
																	100	2.2	7.2
																	200	3.0	9.8
																	400	4.6	15.1
																	700	6.6	21.6
																	900	7.7	25.3
																	1000	8.2	26.9



18 AWG Solid .040" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (60% Coverage)

Gas-injected Foam HDPE Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 80°C)	9248	NEC: CM	U-500	U-152.4	16.5	7.5	18 AWG (solid) .040"	.180	4.57	Duofoil + 60% TC Braid	.270	6.86	75	82%	16.2	53.1	1	.3	1.0
																	10	.7	2.3
																	50	1.5	4.9
																	100	2.0	6.6
																	200	2.8	9.2
																	400	4.0	13.1
																	700	5.3	17.4
																	900	6.1	20.0
																	1000	6.5	21.3
																	1500	8.3	27.2



BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • HDPE = High-density Polyethylene • TC = Tinned Copper • UTP = Unshielded Twisted Pair
Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**. Request quotations of RG/U cables not listed.

†Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.



Standard Analog Video Cable

RG-6/U and RG-11/U Types



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

RG-6/U • 18 AWG Stranded (7x26) .048" Tinned Copper Conductor • Bare Copper Braid Shield (97% Coverage)

Flame-retardant Semi-foam Polyethylene Insulation • Black PVC Jacket																			
80°C	8238	NEC: CM	500	152.4	59.0	26.8	18 AWG (7x26)	.285	7.24	BC Braid	.405	10.29	75	67%	20.5	67.2	1	.2	.6
		CEC: CM	1000	304.8	117.0	53.1	.048"			97% Shield Coverage							10	.7	2.2
							TC			1.2Ω/M'							50	1.3	4.3
							6.1Ω/M'			3.9Ω/km							100	2.0	6.6
							20.0Ω/km										200	2.9	9.5
																	400	4.2	13.8
																	700	5.8	19.0
																	900	6.8	22.3
																	1000	7.1	23.3

Suitable for Indoor and Outdoor applications.

Polyethylene Insulation • Black PVC Jacket

60°C	8261	CEC: CXC	500	152.4	52.5	23.9	18 AWG (7x26)	.285	7.24	BC Braid	.405	10.29	75	66%	20.5	67.2	1	.2	.6
VW-1			1000	304.8	104.0	47.3	.048"			97% Shield Coverage							10	.7	2.2
							TC			1.2Ω/M'							50	1.3	4.3
							6.1Ω/M'			3.9Ω/km							100	2.0	6.6
							20.0Ω/km										200	2.9	9.5
																	400	4.2	13.8
																	700	5.8	19.0
																	900	6.8	22.3
																	1000	7.1	23.3

Suitable for Indoor and Outdoor applications.

Composite • Coax: 18 AWG Solid BC Cond. w/BC Braid Shield (95% Coverage) • **Power: 18 AWG** Stranded (7x26) BC Conductor UTP

Foam Polyethylene Insulation (Coax) • Polypropylene Insulation (Pair) • Black Low-Smoke, Zero-Halogen Jacket																			
Siamese	1306SB	NEC: CMG-LS	500	152.4	37.0	16.8	18 AWG (solid)	.180	4.57	Coax: 95% BC Braid	.275	6.99	75	83%	16.3	53.5	1	.2	.7
300V RMS	new	CEC: CMG-LS FT4 Limited Smoke	1000	304.8	76.0	34.5	.040"			Pair: BC	.514	13.06					10	.6	2.1
							6.4Ω/M'	.059	1.59	10.2Ω/km							50	1.5	4.8
							21.0Ω/km	(Color Code: Black & Red)									100	2.1	6.9
																	200	3.0	9.8
																	400	4.3	14.1
																	700	5.8	19.0
																	900	6.7	22.0
																	1000	7.1	23.3

RG-11/U • 14 AWG Solid .064" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (60% Coverage)

Gas-injected Foam HDPE Insulation • Black PVC Jacket																			
80°C	9292	—	1000	304.8	75.0	34.0	14 AWG (solid)	.280	7.11	Duofoil + 60% TC Braid	.405	10.29	75	84%	16.1	52.8	1	.2	.6
							.064"			3.0Ω/M'							10	.5	1.6
							2.6Ω/M'			9.8Ω/km							50	.9	3.0
							8.5Ω/km										100	1.3	4.3
																	200	1.6	5.3
																	400	2.3	7.6
																	700	3.3	10.8
																	900	4.0	13.1
																	1000	4.3	14.1

Suitable for Indoor and Outdoor applications.

RG-11/U • 14 AWG Solid .064" Bare Copper Conductor • Duofoil (100% Coverage) + Tinned Copper Braid Shield (63% Coverage)

Plenum • Foam FEP Insulation • Black FEP Jacket																			
200°C	89292	NEC: CMP	500	152.4	40.5	18.4	14 AWG (solid)	.274	6.96	Duofoil + 63% TC Braid	.346	8.79	75	83%	16.2	53.1	1	.2	.5
		CATVP	1000	304.8	81.0	36.7	.064"			3.0Ω/M'							10	.4	1.3
		CEC: CMP FT6					BC			9.8Ω/km							50	1.0	3.3
							2.5Ω/M'										100	1.5	4.9
							8.2Ω/km										200	2.2	7.2
																	400	3.3	10.8
																	700	4.5	14.8
																	900	5.2	17.1
																	1000	5.5	18.0

RG-11/U • 14 AWG Solid .064" Bare Copper Conductor • Bare Copper Braid Shield (97% Coverage)

Gas-injected Foam HDPE Insulation • Black Polyethylene Jacket																			
80°C	8213	—	500	152.4	44.0	20.0	14 AWG (solid)	.285	7.24	BC Braid	.405	10.29	75	84%	16.1	52.8	1	.2	.6
			1000	304.8	87.0	39.5	.064"			97% Shield Coverage							10	.4	1.1
			2000	609.6	172.0	78.2	BC			1.1Ω/M'							50	.9	3.0
							2.6Ω/M'			3.6Ω/km							100	1.3	4.3
							8.5Ω/km										200	1.9	6.2
																	400	2.9	9.5
																	700	4.1	13.5
																	900	4.8	15.7
																	1000	5.2	17.1

Suitable for Indoor and Outdoor applications.

BC = Bare Copper • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • HDPE = High-density Polyethylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. 1-800-BELDEN-1. Request quotations of RG/U cables not listed.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com