

# Audio Cable

Commercial Sound/Nurse Call Systems  
Unshielded, Non-Plenum



**Unshielded,  
Pairs or Multi-conductor**  
CM Rated

### Product Description

24 AWG solid bare copper conductors, polypropylene or polyolefin insulation, Dark Gray PVC jacket with rip cord.

**Color Code:** See Charts below.


### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	
Multiconductor	Polypropylene
Paired	Polyolefin
<b>Insulation Thickness</b>	.0065" (.165mm)
<b>Jacket</b>	PVC
<b>Nominal Capacitance</b>	
Multiconductor	17 pF/ft.
Paired	15 pF/ft.
<b>Approvals</b>	
NEC	CM
CEC	CM
<b>Voltage Rating</b>	300V

### Applications

- Nurse Call Systems
- Commercial Sound Systems
- Annunciators
- Voice Systems
- Paging

#### Paired



#### Multi-conductor



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

**Unshielded, Paired (NEC CM and CEC CM FT1)**

<b>24 AWG, Cat. 5e</b>										
<b>5662UG</b> <small>NEW</small>	6	solid	1000	304.8	16.0	8.62	—	—	.172	4.37
	(3/pr)									

**Unshielded, Multi-conductor (NEC CM and CEC CM)**

<b>24 AWG</b>										
<b>5626UG</b> <small>NEW</small>	8	solid	1000	304.8	29.0	13.15	.030	.762	.093	2.36
									x	x
									.324	8.23
<b>5624UG</b> <small>NEW</small>	6	solid	1000	304.8	19.0	8.62	.024	.610	.081	2.06
									x	x
									.246	6.25

#### Color Code Chart

(5662UG)

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green

#### Color Code Chart

(5626UG)

Cond. No.	Color
1	Yellow
2	Blue
3	Black
4	Orange
5	Red
6	Green
7	White
8	Purple

#### Color Code Chart

(5624UG)

Cond. No.	Color
1	Blue
2	Black
3	Orange
4	Red
5	Green
6	White

# Audio Cable

Commercial Sound/Nurse Call Systems  
Unshielded, Plenum-Rated



**Unshielded,  
Pairs or Multi-conductor**  
CMP Rated

### Product Description

24 AWG solid bare copper conductors, FEP insulation, Dark Gray Flammarrest® jacket with rip cord.

**Color Code:** See Charts below.


### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	FEP
<b>Insulation Thickness</b>	.007" (.178mm)
<b>Jacket</b>	Flammarrest
<b>Nominal Capacitance</b>	15 pF/ft.
<b>Approvals</b>	
NEC	CMP
CEC	CMP FT6
<b>Voltage Rating</b>	300V

### Applications

- Nurse Call Systems
- Commercial Sound Systems
- Annunciators
- Voice Systems
- Paging

#### Paired



#### Multi-conductor



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Plenum-rated, Unshielded, Pairs (NEC CMP and CEC CMP FT4, FT6)

24 AWG, Cat. 5e										
<b>6662UG</b> <small>NEW</small>	6	solid	1000	304.8	23.0	10.4	—	—	.165	4.19

#### Plenum-rated, Unshielded, Multi-conductor (NEC CMP and CEC CMP FT6)

24 AWG										
<b>6626UG</b> <small>NEW</small>	8	solid	1000	304.8	28.0	12.70	.019	.483	.072	1.83
									X	X
									.310	7.87
<b>6624UG</b> <small>NEW</small>	6	solid	1000	304.8	21.0	9.53	.019	.483	.072	1.83
									X	X
									.246	6.25

#### Color Code Chart

(6662UG)

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green

#### Color Code Chart

(6626UG)

Cond. No.	Color
1	Yellow
2	Blue
3	Black
4	Orange
5	Red
6	Green
7	White
8	Purple

#### Color Code Chart

(6624UG)

Cond. No.	Color
1	Blue
2	Black
3	Orange
4	Red
5	Green
6	White